



Teksperse NS3

High molecular weight polymeric dispersant with high cationic functionality

Description:

Teksperse NS3 is a high molecular weight polymer of hydrophobic type dispersion agent designed as wetting and dispersing agent for solvent. Teksperser NS3 is a 100% active version of Teksperser BM3. Teksperser NS3 prevents reflocculation of pigments through steric hindrance and therefore stabilizes the color strength and hue of pigments in paints and pigment concentrates system. Its high concentration of pigment affinic groups improves the wetting and dispersing to give a very low millbase viscosity even at a low dosage. Teksperser NS3 designed to disperse difficult organic pigment especially high color carbon black. Dispersion of carbon black results in coating with very high jetness and blue tone. The dispersion agent also can be used for other colors such as red, blue, green, and yellow.

Physical constant:

| | |
|--------------------------|--------------------------------------|
| Appearance | Clear, low viscosity solution |
| Percent active, % | 100 |
| Solvents | None |

Application:

Teksperse NS3 can be used in all types of solvent base coatings such as automotive, high performance industrial coatings, coil coatings, and others. Teksperser NS3 is especially design to give good dispersion, color performance, and stability in UV system. Teksperser NS3 is compatible to difference resin chemistries particularly acrylic, polyester, and alkyd (long, medium, and short chain).

Recommend Dosage:

High color carbon black (Cabot M1300 or Degussa FW200 type)

40-60% active on carbon black or 1 part of wet dispersant to 1 part of pigment

Medium color carbon black (Cabot M900 or Degussa SS6 type)

20-40% active on carbon black or 0.75 part of wet dispersant to 1 part of pigment

Regular color carbon black (Cabot R400, Degussa SS4, or MA100 type)

10-15% active on carbon black or 0.25 part of wet dispersant to 1 part of pigment

Other colors pigment

10-20% active on carbon black or 0.30 part of wet dispersant to 1 part of pigment

Inorganic pigment

5-10% active on carbon black or 0.10 part of wet dispersant to 1 part of pigment

The information in this data sheet is, to the best of our knowledge, true and accurate, but all recommendations and suggestions are made without guarantee since conditions of use and storage after leaving our possession are beyond our control. Chem-Teks disclaims any liability incurred in connection with the use of these products and recommendations.